



SPECIFICATIONS

- 1、 Current Rating: 1A AC, DC
- 2、 Voltage Rating: 100V AC, DC
- 3、 Temperatuer Range: -25°C ~ +85°C
- 4、 Contact Resistance: 20mΩ Max
- 5、 Insulation Resistance: 500mΩ Min
- 6、 Withstanding Voltang: 500V AC/minute
- 7、 Material:Housing:Nylon66, UL94V-0

| P 数 | 尺寸 (mm) |       |
|-----|---------|-------|
|     | A       | B     |
| 02Y | 1.50    | 4.50  |
| 03Y | 3.00    | 6.00  |
| 04Y | 4.50    | 7.50  |
| 05Y | 6.00    | 9.00  |
| 06Y | 7.50    | 10.50 |
| 07Y | 9.00    | 12.00 |
| 08Y | 10.50   | 13.50 |
| 09Y | 12.00   | 15.00 |
| 10Y | 13.50   | 16.50 |
| 11Y | 15.00   | 18.00 |
| 12Y | 16.50   | 19.50 |
| 15Y | 21.00   | 24.00 |

|  |  |  |   |                    |                  |
|--|--|--|---|--------------------|------------------|
| <p>一般公差<br/>TOLERANCES<br/>X. ±0.40 .XX ±0.20<br/>.X ±0.30 .XXX ±0.10<br/>ANGLES ±2°</p> |  |  | <p>深圳市宏利电子有限公司<br/>Shenzhen Holy Electronic Co.,Ltd</p> |                    |                  |
| <p>检验尺寸标示<br/>SYMBOLS   INDICATE CLASSIFICATION DIMENSION</p>                            |  | <p>工程图号<br/>ZH15HG-nY</p>              | <p>制图 (DR)<br/>10/03/22</p>                             |                    |                  |
| <p> MARK IS CRITICAL DIM.<br/> MARK IS MAJOR DIM.</p>                                    |  | <p>品名<br/>ZH1.5-nY 胶壳</p>              | <p>审核 (CHKD)</p>  |                    |                  |
| <p>表面处理 (FINISH)</p>   |  | <p>TITLE<br/>ZH1.5mm Pitch Housing</p> | <p>核准 (APPD)<br/>Rigo Lu</p>                            |                    |                  |
| <p>比例 (SCALE)<br/>1:1</p>  |  | <p>单位 (UNITS)<br/>mm</p>               | <p>张数 (SHEET)<br/>1 OF 1</p>                            | <p>SIZE<br/>A4</p> | <p>REV<br/>0</p> |

| 修订<br>REV | 修改摘要<br>REVISION DESCRIPTION | 日期<br>DATE | 签名<br>SIGNATURE |
|-----------|------------------------------|------------|-----------------|
| -         | -                            | -          | -               |